



Material:

Insulator: Glass filled Polyester UL 94V-0

Contact: Copper alloy

Shell: Steel, Tin plated as standard

Ordering Code

11W1 P0 S0 A 100 000
 ① ② ③ ④ ⑤ ⑥

① Series No.

② Connector Type:

P0= Plug

③ Contact tail Style:

S0= Solder Cup type

④ Singal Contact Plating:

A= Seletive Gold flash plated over Nickel

B= Seletive 15 μ " Gold plated over Nickel

C= Seletive 30 μ " Gold plated over Nickel

⑤ Insulator Color:

100= Black

600= Green

⑥ Mounting Style:

000= With ϕ 3.05mm holes on shell

A00= Riveted #4-40 UNC close nuts on front shell

B00= Riveted #4-40 UNC open nuts on front shell

C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style

RoHS Compliant

Code	000	Code	A00	Code	B00	Code	C00
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

④					DATE	UNIT: mm / inch	TITLE: 11W1 MALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	瀚荃股份有限公司 CviLux Corporation	
③				DRAWN BY: James	11/18-02'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:		
②				ENGINEER: David	11/19-02'	.X \pm 0.30/.012 .X' \pm 1'			
①				CHECKED BY: David	11/19-02'	.XX \pm 0.20/.008 .X' \pm	FINISH:		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	11/19-02'	.XXX \pm 0.10/.004 .XX' \pm	DRAWING NO. 11W101SC	PART NO. 11W1P0S0**00*00	
							SCALE	2 / 1	SHEET 1 OF 1

