



A = 3.96 x No. of Spaces

B = A + 3.96

* Available in 2 through 24 circuits

Material:

* Insulation: Glass filled polyester UL 94V-0
Color White(Nature)

* Contact: Brass

Ordering Code:

CI82 ** P * V 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
1= 3.05µm(120µ") Min. Tin
over 0.76µm(30µ") Nickel
2= Gold flash plated over
1.27µm(50µ") Nickel
3= 0.38µm(15µ") Gold plated
over 1.27µm(50µ") Nickel
4= 0.76µm(30µ") Gold plated
over 1.27µm(50µ") Nickel
- ⑤ Tail Style: V= Straight
- ⑥ Option: 00= Standard

Recommended P.C. Board Layout

RoHS Compliant

4						DATE	UNIT: mm / inch	TITLE: 3.96MM(.156") STRAIGHT DIP HEADER	 瀚荃股份有限公司 CviLux Corporation	
3			DRAWN BY: Sun		11/02-04'	TOLERANCE UNLESS OTHERWISE SPECIFIED				
2			ENGINEER: Eisley		11/04-04'	.X ± 0.38/.015	X' ± 1'	MATERIAL:		
1	SUN	9/30/03'	ECN03330/ECR03030-0		CHECKED BY: David	11/04-04'	.XX ± 0.25/.010	.X' ±		FINISH:
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	11/04-04'	.XXX ± 0.10/.004	.XX' ±		DRAWING NO. CI8201SD	PART NO. CI82**P*V00
									SCALE 2 / 1	SHEET 1 OF 1