



A = 3.96 x No. of Spaces
 B = A + 3.96
 * Available in 2 through 24 circuits

Material:

* Insulation: Glass filled polyester UL 94V-0
 Color White(Nature)

* Contact: Brass

Ordering Code:

$\frac{C182}{①} \frac{**}{②} \frac{P}{③} \frac{*}{④} \frac{H}{⑤} \frac{00}{⑥}$

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 - 1= 3.05µm(120µ") Min. Tin over 0.76µm(30µ") Nickel
 - 2= Gold flash plated over 1.27µm(50µ") Nickel
 - 3= 0.38µm(15µ") Gold plated over 1.27µm(50µ") Nickel
 - 4= 0.76µm(30µ") Gold plated over 1.27µm(50µ") Nickel
- ⑤ Tail Style: H= Right angle
- ⑥ Option: 00= Standard

Recommended P.C. Board Layout

RoHS Compliant

					DATE	UNIT: mm / inch	TITLE: 3.96MM(.156") RIGHT ANGLE HEADER	 瀚荃股份有限公司 CviLux Corporation	
					DRAWN BY: Sun	10/03-03'	TOLERANCE UNLESS OTHERWISE SPECIFIED		
					ENGINEER: Eisley	10/06-03'	.X ± 0.38/.015 X.' ± 1'		
					CHECKED BY: David	10/08-03'	.XX ± 0.25/.010 .X' ±		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/08-03'	.XXX ± 0.10/.004 .XX' ±	FINISH:	DRAWING NO. C18202SD	PART NO. C182**P*H00
								SCALE 2 / 1	SHEET 1 OF 1

CVILUX.CORP
 2003.10.08
 ISSUED