



A = 2.54 x No. of Spaces

B = A + 2.54

* Available in 2 through 36 circuits

Material:

* Insulation: Glass filled polyester UL 94V-0
Color White(Nature)

* Contact: Brass

Ordering Code:

CI83 ** P * H 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 - 1= 3.05μm(120μ") Min. Tin over 0.76μm(30μ") Nickel
 - 2= Gold flash plated over 1.27μm(50μ") Nickel
 - 3= 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
 - 4= 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ⑤ Tail Style: H= Right angle
- ⑥ Option: 00= Standard

Recommended P.C. Board Layout

RoHS Compliant

					DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") RIGHT ANGLE HEADER	 瀚荃股份有限公司 CviLux Corporation
					DRAWN BY: Jim	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
					ENGINEER: Eisley	.X ± 0.30/.012 X.' ± 1"	FINISH:	
					CHECKED BY: David	.XX ± 0.20/.008 .X' ±	DRAWING NO. CI8302SD PART NO. CI83**P*H00	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	DATE	.XXX ± 0.10/.004 .XX' ±	SCALE 3 / 1	SHEET 1 OF 1

CVILUX.CORP
2006.03.20
ISSUED