

Back View

Material:

- \* Insulation: PBT + 30% GF. UL 94V-0 ,Color Black
- \* Cover: PBT + 15% GF. UL 94V-0 ,Color Nature
- \* Contact: Phosphor Bronze



Ordering Code:

CI94 P FM \* 1 \*0  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② P= Power
- ③ FM= Female Molding TYPE
- ④ Plating code:  
 A= Selective Gold flash plated over 50μ" Nickel  
 B= Selective 15μ" Gold plated over 50μ" Nickel  
 C= Selective 30μ" Gold plated over 50μ" Nickel
- ⑤ Color: 1= Black
- ⑥ Other option: 00= AWG#18 - AWG#22  
 A0= AWG#18x2 - AWG#22x2

Tin-Lead Process

RoHS Compliant

⑤	Sandy	11/10-10'	ECN10365		DATE	UNIT: mm / inch	TITLE: SERIAL ATA POWER MOLDING TYPE RECEPTACLE CONN. (SOLDER TYPE)	 瀚荃股份有限公司 CviLux Corporation	
④	Sandy	12/11-08'	ECN08607		DRAWN BY: Sandy	11/11-10'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:
③	Sandy	12/27-07'	ECN07551/ECR07106-1		ENGINEER: Clark	11/23-10'	.X ± 0.30/.012 X: ± 1'		FINISH:
②	Sun	7/11/05'	ECN05232		CHECKED BY: David	11/23-10'	.XX ± 0.20/.010 .X: ±	DRAWING NO. CI9408SE PART NO. CI94PFM*1*0	
SYM	NAME	DATE	REVISIONS		APPROVED BY: David	11/23-10'	.XXX ± 0.10/0.04 .XX: ±	SCALE 2 / 1 SHEET 1 OF 1	