



Back View

Material:

- \* Insulation: PBT + 15% GF. UL 94V-0 ,Color Black
- \* Cover: Nylon66 UL 94V-0 ,Color Black
- \* Contact: Phosphor Bronze

Ordering Code:

CI94 P FM \* 1 \*P - NH  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② P= Power
- ③ FM= Female Molding TYPE
- ④ Plating code:  
 A= Selective Gold flash plated over 50μ" Nickel  
 B= Selective 15μ" Gold plated over 50μ" Nickel  
 C= Selective 30μ" Gold plated over 50μ" Nickel
- ⑤ Color: 1= Black
- ⑥ Other option: OP= AWG#18 - AWG#22  
 AP= AWG#18x2 - AWG#22x2
- ⑦ -NH= Halogen-Free

Halogen-Free

RoHS Compliant

CIVILUX CORP  
 2009.12.29  
 ISSUED

④					DATE	UNIT: mm / inch	TITLE: SERIAL ATA POWER MOLDING TYPE RECEPTACLE CONN. (SOLDER TYPE)	 瀚荃股份有限公司 CviLux Corporation
③				DRAWN BY: Hank	12/22-09'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Eisley	12/22-09'	.X ± 0.30/.012 X' ± 1'	FINISH:	
①				CHECKED BY: Eisley	12/22-09'	.XX ± 0.20/.010 .X' ±		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	12/22-09'	.XXX ± 0.10/0.04 .XX' ±		DRAWING NO. CI9427SA PART NO. CI94PFM*1*P-NH
								SCALE 2 / 1 SHEET 1 OF 1