



Recommended PC Board Layout

Materials :

Insulator : Glass filled Polyester UL 94V-0

Contact : Phosphor Bronze, Selective Gold plated in contact area over 100 micro-inches Nickel plated

Ordering Code

CJ46 8* * 1 1 0*
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts: 84=8P4C, 86=6P6C, 88=8P8C
- ③ Plating option:
 - A= Selective 0.03μm(1.2μ") Gold flash plated over 1.27μm(50μ")Nickel
 - B= Selective 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
 - C= Selective 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
 - E= Selective 1.27μm(50μ") Gold plated over 1.27μm(50μ") Nickel
- ④ 1= Single port
- ⑤ Insulator Color: 1= Black
- ⑥ Other options: 00= Standard, OK= With Key

RoHS Compliant

④	Sun	9/30/05	ECR05067-0/ECN05275		DATE	UNIT: mm / inch	TITLE: BOARD MOUNT TOP ENTRY PCB JACK	 瀚荃股份有限公司 CviLux Corporation	
③	SUN	5/16/05'	ECN05173		DRAWN BY: Jim	9/7 06'	TOLERANCE UNLESS OTHERWISE SPECIFIED		MATERIAL:
②	SUN	5/21/04'	ECN04205/ECR04047-0		ENGINEER: Eisley	9/7 06'	.X ± 0.30/012 .X' ± 1"		FINISH:
⑤	Jim	9/7/06'	ECR06080-0/ECN06316		CHECKED BY: David	9/7 06'	.XX ± 0.20/008 .X' ±		
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	9/7 06'	.XXX ± 0.08/003 .XX' ±		DRAWING NO. CJ4601SH PART NO. CJ468**110*
								SCALE 1 / 1 SHEET 1 OF 1	