



Material:
 * Insulation: Nylon 66, Color Nature
 * Contact: Brass
 Circuit Pattern Schedule: See Drawing No: CP0110S*

Ordering Code:

CP-01 3 ** * * 0
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Type of Connector: 3= Straight PCB mount header
- ③ No. of Circuits: See below table
- ④ Plating Code:
 1= 2.54μm(100μ") Tin over 1.02μm(40μ") Nickel
 2= Gold flash plated over 0.76μm(30μ") Nickel
 B= Selective 0.38μm(15μ") gold plated over 1.27μm(50μ") Nickel
 C= Selective 0.76μm(30μ") gold plated over 1.27μm(50μ") Nickel
- ⑤ Variation:
 4= UL 94V-2, With mounting pegs
 5= UL 94V-0, With mounting pegs
- ⑥ Other option:
 0= Standard

Recommended P.C. Board Layout

④						DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER	瀚荃股份有限公司 CviLux Corporation
③						DRAWN BY: Casey	TOLERANCE UNLESS OTHERWISE SPECIFIED	CP-01 POWER CONNECTOR	
②						ENGINEER: Eisley	.X ± 0.38/.015 X' ± r'	MATERIAL:	
①						CHECKED BY: David	.XX ± 0.25/.010 .X' ±	FINISH:	
SYM	NAME	DATE	REVISIONS			APPROVED BY: Alex	.XXX ± 0.10/.004 .XX' ±		
									DRAWING NO. CP0130SJ
									PART NO. CP-013***40
									CP-013***50
							SCALE	2 / 1	SHEET 1 OF 1

CVILUX CORP.
 2004.02.09
 ISSUED