



Material:

* Insulation: Nylon 66, Color Nature

* Contact: Brass

Circuit Pattern Schedule: See Drawing No: CP0110S*

Ordering Code:

CP-01 3 ** * G 0
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Type of Connector: 3= Straight PCB mount header
- ③ No. of Circuits: See below table
- ④ Plating Code:
 1= 2.54 μ m(100 μ ”) Tin over 1.02 μ m(40 μ ”) Nickel
 2= Gold flash plated over 0.76 μ m(30 μ ”) Nickel
 B= Selective 0.38 μ m(15 μ ”) gold plated over 1.27 μ m(50 μ ”) Nickel
 C= Selective 0.76 μ m(30 μ ”) gold plated over 1.27 μ m(50 μ ”) Nickel
- ⑤ Variation:
 G= UL 94V-2, With mounting pegs (Glow wire available)
- ⑥ Other option:
 0= Standard

Recommended P.C. Board Layout

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER	瀚荃股份有限公司 CviLux Corporation	
③				DRAWN BY: Sandy	7/06-07'	TOLERANCE UNLESS OTHERWISE SPECIFIED	CP-01 POWER CONNECTOR		
②				ENGINEER: Eisley	7/06-07'	.X ± 0.38/.015 X' ± r'	MATERIAL:		
①				CHECKED BY: David	7/06-07'	.XX ± 0.25/.010 X' ±	FINISH:		
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	7/06-07'	.XXX ± 0.10/.004 XX' ±	DRAWING NO. CP0151AA	PART NO. CP-013***GO	
								SCALE 2 / 1	SHEET 1 OF 1

CVILUX CORP.
 2007.07.10
 ISSUED