



| Part No. | Wire Range | Insulation Diameter | Reel Q'ty |
|-------------|-------------|---------------------|------------|
| CP04T021PE0 | AWG #22~#28 | 1.60 (.063) MAX. | 4,000 PCS. |
| CP04T031PE0 | AWG #18~#22 | 2.10 (.083) MAX. | 4,000 PCS. |

Ordering Code:

CP04 T02 1 P E 0
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Type: T02= AWG #22 ~ #28
T03= AWG #18 ~ #22
- △ ③ Plating: 1= 30u" Min. Tin plated (Reflow Plated)
- ④ Material: P= Phosphor Bronze
- ⑤ Plating method: E= Pre-tinned
- ⑥ Option: 0= Standard

SEC. A-A

SEC. B-B

SEC. A-A

SEC. B-B

(P/N : CP04T031PE0)

(P/N : CP04T021PE0)

BACK VIEW

| SYM | NAME | DATE | REVISIONS | APPROVED BY: | DATE |
|-----|-------|----------|-----------------------|--------------|------|
| △4 | Sandy | 9/26-19' | ECNT116218/ECRB116066 | | |
| △3 | Erin | 5/7-12' | ECR12021-0/ECN12074-0 | | |
| △2 | Sandy | 5/11-07' | ECN07189/ECR07031-2 | | |
| △1 | Sun | 4/11-07' | ECR07056-0/ECN07133 | | |



| | | |
|--------------|--------|----------|
| DRAWN BY: | Sandy | 9/30-16' |
| ENGINEER: | Sun | 10/3-16' |
| CHECKED BY: | Eisley | 10/3-16' |
| APPROVED BY: | Eisley | 10/3-16' |

| UNIT: mm / inch | |
|--------------------------------------|---------|
| TOLERANCE UNLESS OTHERWISE SPECIFIED | |
| .X ± 0.20/008 | X' ± 1" |
| .XX ± 0.10/004 | .X ± |
| .XXX ± 0.05/002 | .XX ± |

| | |
|-----------|----------------|
| TITLE: | CRIMP TERMINAL |
| MATERIAL: | |
| FINISH: | |



瀚荃股份有限公司
CviLux Corporation

| | | | |
|-------------|----------|----------|----------------------------|
| DRAWING NO. | CP0403SE | PART NO. | CP04T021PE0 CP04T031PE0 |
| SCALE | 6 / 1 | SHEET | 1 OF 1 |