



Circuits	Dimension			
	A	B	C	D
2	4.00	10.00	6.50	4.00
	8.00	14.00	10.50	8.00
	12.00	18.00	14.50	12.00
	16.00	22.00	18.50	16.00
3	4.00	14.00	10.50	8.00
	8.00	22.00	18.50	16.00
4	4.00	18.00	14.50	12.00
5	4.00	22.00	18.50	16.00

Ordering Code:

CP04 2 A P 1 M L 0 -LF
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Circuits: 2, 3, 4 & 5 Pin
- ③ Circuits pitch:
A= 4.0mm, B= 8.0mm, C= 12.0mm, D=16.0mm
- ④ P= Pin Header
- ⑤ Plating Code:
1= Matte Tin Plated
- ⑥ Contact type: M= SMT Type
- ⑦ Option: L= Locking Type
- ⑧ Other option: 0= Standard(Reel Packing)
- ⑨ LF= For Lead Free soldering process

Material:

Insulator:

Nylon 6T + 30% G.F UL 94V-0

Color Nature(Ivory)

Contact: Brass

Tab: Brass

Lead Free Process

RoHS Compliant

SYM	NAME	DATE	REVISIONS	APPROVED BY:	DATE	UNIT: mm / inch	TITLE: 4.0/8.0/12.0/16.0mm PITCH WIRE TO BOARD CONNECTOR	DRAWING NO. CP0419SE	PART NO. CP04**P1MLO-LF
△4	Eisley	5/2/07'	ECN07120			UNIT: mm / inch	TITLE: 4.0/8.0/12.0/16.0mm PITCH WIRE TO BOARD CONNECTOR		
△3	Jim	12/1/06	ECN06443	DRAWN BY:	Eisley	5/2/07'	TOLERANCE UNLESS OTHERWISE SPECIFIED		
△2	Jim	11/7/06	ECN06410	ENGINEER:	Eisley	5/2/07'	.X ± 0.30/.012 X' ± r'		
△1	Sun	8/25/06	ECN06289	CHECKED BY:	David	5/2/07'	.XX ± 0.20/.008 .X' ±		
				APPROVED BY:	Alex	5/2/07'	.XXX ± 0.10/.004 .XX' ±	FINISH:	SCALE 3 / 1
								SHEET 1 OF 1	

