



Materials :

- * Insulator : Glass filled polyester UL 94V-0
- * Contact : Brass
- * Shield : Brass with Nickel plated
- * Solder tail plating : Tin plated over Nickel

Ordering Code

CE52 06 S A 1 00-C
 ① ②③④⑤ ⑥

- ① Series No.
- ② Contacts: 03~08 Circuits
- ③ Connector type: S=Receptacle
- ④ Plating code:
 A=Selective Gold flash plated over 1.27μm(50μ") Nickel
 B=Selective 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel
 C=Selective 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ⑤ Color code: 1=Black, 6=Green, 8=Purple
- ⑥ Other option: 00-C=With grounding hook

Circuits	3	4	5	6	7	8
Arrangement of Contact						
P.C Board Layout						
Tolerance	.X ± 0.10/.004 .XX ± 0.05/.002					

Lead Free Process
 RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: FULLY SHELED MINI DIN SOCKET WITH HOOK & GROUNDING	瀚荃股份有限公司 CviLux Corporation
③					DRAWN BY: Enya 9/18-12'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②					ENGINEER: Easley 9/18-12'	.X ± 0.38/.015 .X ± 2.0°	FINISH:	DRAWING NO. CE5203SB PART NO. CE52**S**00-C
①	Enya	9/18-12'	ECN12231-0/ECR12064-0	CHECKED BY: Easley 9/18-12'	APPROVED BY: David 9/18-12'	.XX ± 0.25/.010 .XX ± 1.0°		SCALE 3 / 1
SYM	NAME	DATE	REVISIONS	APPROVED BY:	DATE	.XXX ± 0.13/.005 .XXX ± 0.5°		

CVILUX CORP
 2012.10.11
 ISSUED