



Materials :

- * Insulator : Glass filled polyester UL 94V-0
- * Contact : Brass
- * Shell : Copper Alloy
- * Shell Plating: 50~80 μ ” Nickel over 50 μ ” Cu
- * Ground Strap : Stainless steel
- * Solder tail plating : Tin plated over Nickel

Ordering Code CE56 06 S A 1 KO-C

- ① Series No.
- ② Contacts: 03~08 Circuits
- ③ Connector type: S=Receptacle
- ④ Plating code:
 A=Selective Gold flash plated over 1.27 μ m(50 μ ”) Nickel
 B=Selective 0.38 μ m(15 μ ”) Gold plated over 1.27 μ m(50 μ ”) Nickel
 C=Selective 0.76 μ m(30 μ ”) Gold plated over 1.27 μ m(50 μ ”) Nickel
- ⑤ Color code: 1=Black, 6=Green, 8=Purple
- ⑥ Other option: KO-C=With grounding pegs

Circuits	3	4	5	6	7	8
Arrangement of Contact						
P.C Board Layout						
Tolerance	.X \pm 0.10/.004 .XX \pm 0.05/.002					

Lead Free Process
RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: FULLY SHEILED MINI DIN SOCKET WITH GROUNDING & HOOK	瀚荃股份有限公司 CviLux Corporation
③					DRAWN BY: Enya	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②					ENGINEER: Easley	.X \pm 0.38/.015 .X' \pm 2.0'	FINISH:	DRAWING NO. CE5603SB
①	Enya	9/18-12'	ECN12231-0/ECR12064-0	CHECKED BY: Easley	9/18-12'	.XX \pm 0.25/.010 .XX' \pm 1.0'		PART NO. CE56**S**KO-C
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	9/18-12'	.XXX \pm 0.13/.005 .XXX' \pm 0.5'	SCALE	3 / 1
								SHEET 1 OF 1

CIVILUX CORP
2012.10.11
ISSUED