


Material:
 * Insulation: PBT+ 15% GF. UL 94V-0
 * Contact: Phosphor Bronze

Ordering Code:

CS01 50 2 A 1 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Isulation high:
- ③ Plating option:
2= Gold flash plated over 1.27μm(50μ”) Nickel
- ④ Contact type:
A= Closed ead
- ⑤ Color code:
1= Black ,3= Red ,7= Blue
- ⑥ Option:
00= Standard

RoHS Compliant

④						UNIT: mm / inch	TITLE: 2.00MM(.079") LOW PROFILE CLOSED TOP SHUNT	 瀚荃股份有限公司 CviLux Corporation
③	Enya	5/8-13'	ECR13036-0/ECN13103-0	2013.05.23 ISSUED	DRAWN BY: Enya	5/08-13'	TOLERANCE UNLESS OTHERWISE SPECIFIED	
②	Sandy	5/5-09'	ECN09224		ENGINEER: Eisley	5/10-13'	.X ± 0.30 / .012 X* ± 1*	DRAWING NO. CS0103SD PART NO. CS01502A*00
①	SUN	9/30/05	ECR05067-0/ECN05275		CHECKED BY: Eisley	5/10-13'	.XX ± 0.20 / .008 .X* ±	
SYM	NAME	DATE	REVISIONS		APPROVED BY: David	5/10-13'	.XXX ± 0.10 / .004 .XX* ±	SCALE 10 / 1 SHEET 1 OF 1