

Material:

* Insulation: PBT+ 15% GF. UL 94V-0

④⑥ * Contact: Brass


③

Ordering Code:

CS01 60 2 B 1 00
① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Isulation high:
- ③ Plating option:
2= Gold flash plated over
1.27 μ m(50 μ ") Nickel
- ④ Contact type:
B= Open end
- ⑤ Color code:
1= Black, 3= Red, 5= Yellow
6= Green, 7= Blue
- ⑥ Option:
00= Standard

RoHS Compliant

⑥	Karen	9/03-15'	ECNT115201/ECRT115071		DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") OPEN TOP SHUNT	 瀚荃股份有限公司 CviLux Corporation
⑤	Enya	5/8-13'	ECR13036-0/ECN13103-0	DRAWN BY: Karen	9/03-15'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
④	Sandy	7/22-10'	ECN10266	ENGINEER: Sun	9/04-15'	.X ± 0.30 / .012 X' ± 1"	FINISH:	DRAWING NO. CS0104SG PART NO. CS01602B*00
③	Sandy	5/5/09'	ECN09224	CHECKED BY: Eisley	9/04-15'	.XX ± 0.20 / .008 .X' ±		SCALE 10 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	9/04-15'	.XXX ± 0.10 / .004 .XX' ±		

CVILUX CORP
2015.09.10
ISSUED