



Notes:  
 Insulator: Glass filled Polyester UL 94V-0  
 Contact: Copper alloy  
 Shell: Steel, Tin plated as standard  
 High power Contact :  
 Brass with Gold plated  
 \*For Lead Free Wave Flow Process

### Ordering Code

11W1 P P H 3 2 1 40 I10  
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: P= Plug
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ High power contact plating:  
 2= Gold flash plated over Nickel  
 3= 15 $\mu$ " Gold plated over Nickel  
 4= 30 $\mu$ " Gold plated over Nickel  
 5= 50 $\mu$ " Gold plated over Nickel
- ⑥ Signal contact plating:  
 2= Gold flash plated over Nickel  
 3= 15 $\mu$ " Gold plated over Nickel  
 4= 30 $\mu$ " Gold plated over Nickel
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 40= 40A
- ⑨ Mounting Style:  
 000= With  $\phi$ 3.05mm holes on shell  
 B00= Riveted #4-40 UNC open nuts on front shell  
 C00= Riveted #4-40 UNC open nuts on rear shell  
 I00= Riveted #4-40 UNC ground tabs with  $\phi$ 3.2mm holes  
 I10= Riveted #4-40 UNC ground tabs with board locks(standard)

### Mounting Style

Code	000	Code	B00	Code	C00	Code	I00	Code	I10
			DIM. L= 4.0mm		DIM. L= 4.0mm		$\phi$ A=3.2mm		

Lead Free Process

RoHS Compliant

④	Karen	4/07-17'	ECNT117049/ECRT117003		DATE	UNIT: mm / inch	TITLE: 11W1 40A HIGH POWER MALE D-SUB CONNECTOR (RIGHT ANGLE TYPE)	瀚荃股份有限公司 CviLux Corporation	
③	Sun	12/10-08	ECN08604	DRAWN BY: Karen	4/10-17'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:		
②	Jim	10/13/06	ECR06094-0/ECN06369	ENGINEER: Sun	4/10-17'	.X ± 0.30/.012 X: ± 1'	FINISH:	SCALE 2 / 1	SHEET 1 OF 1
①	Sun	3/24/05'	ECR05025-0/ECN05095	CHECKED BY: Eisley	4/14-17'	.XX ± 0.20/.008 X: ±			
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	4/14-17'	.XXX ± 0.10/.004 XX ±			

CVILUX CORP  
 2017.04.20  
 ISSUED