

Cl23 Series 2.50mm(.098") Wire to Board Connectors DIP Headers


- With locking wall
- Mate with Cl23 Housing
- O Insulator: Nylon 66 UL 94V-2, Color Ivory
- With Tin plated 0.64mm square pin


















Straight












(2 Through 5 Circuits)

(6 Through 12 Circuits)

Circuits	Dimension	
	А	В
2	2.5(.098)	5.0(.197)
3	5.0(.197).	7 5(.295)
4	7.5(.295)	10.0(.394)
5	10.0(.394)	12.5(.492)
6	12.5(.492)	15.0(.591)
7	15.0(.591)	17.5(.689)
8	17.5(.689)	20.0(.787)
9	20.0(.787)	22.5(.886)
10	22.5(.886)	25.0(.984)
11	25.0(.984)2	7.5(1.083)
12	27.5(1.083)	30.0(1.181)

Right Angle







(2 Through 5 Circuits)



(6 Through 12 Circuits)

1ST Circuit Position 9.8 .386 2.0

2.5±0.05 .098±.002 ++φ1.20±0.05 TYP. .047±.002

Recommended P.C. Board Layout

Ordering Code

C I 2 3











- Series No.
- 2 No. of Circuits: 02 to 12
- 3 P = DIP Type
- Plating Code:
 - 1 = Tin over Nickel

- **6** Type: V = Straight
 - H = Right Angle
 - **6** Other Options:
 - 00 = Standard
 - *Special options consult manufacturer