

CBRD Series 0.80mm(.032") Board To Board Connectors

MOQ: 5000pcs but also based on MPQ

Mating Height	Plug	Receptacle
<p>4.0 .157</p>	<p>2.35 .093</p> <p>P/N:CBRD***PA2FP1R0-NH</p>	<p>3.4 .134</p> <p>P/N:CBRD***SA2FP1R0-NH</p>
<p>5.0 .197</p>	<p>2.35 .093</p> <p>P/N:CBRD***PA2FP1R0-NH</p>	<p>4.4 .173</p> <p>P/N:CBRD***SB2FP1R0-NH</p>
<p>8.0 .315</p>	<p>2.35 .093</p> <p>P/N:CBRD***PA2FP1R0-NH</p>	<p>7.4 .291</p> <p>P/N:CBRD***SE2FP1R0-NH</p>

Ordering Code

1 2 3 4 5 6 7 8 9 10
C B R D 0 8 0 S A 2 F P 1 R 0 - N H

- 1** Series No.
- 2** No. of Circuits: 010 to 080
(Available: 10,12,14,16,20,24,30, 34,36,40,50,60,80)
*Circuits not found above please consult manufacturer
- 3** Connector Type: P = Plug
S = Receptacle

- 4** Height:
Plug: A: DIM.E = 2.35mm
Receptacle: A: DIM.E = 3.40mm
B: DIM.E = 4.40mm
E: DIM.E = 7.40mm

- 5** Plating Code:
2 = Gold flash over Nickel

- 6** Fixed Tab Options:
0 = Without Fixed Tab
F = With Fixed Tabs
- 7** Pegs Options: 00 = Without Peg
P1 = With Pegs
- 8** Packing Options: R = Tape & Reel
- 9** Other Options: 0 = Standard
- 10** -NH = For Lead Free IR process and Halogen-Free

CB

BOARD TO BOARD