

ENGINEERING	PRODUCT SPECIFICATION For 1.27 mm (.050") Center Spacing Flat Cable - IDC Dip Plug	SPEC.NO.: SPCA003B
DEPT.		PAGE: 1/2

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202 Methods for test of connectors for electronic equipment
MIL - STD - 1344 Test methods for electrical connectors

3. APPLICABLE SERIES NO.: CA05 Series

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. APPLICABLE CABLES

0.635 mm (.025") center spacing Flat Cable

Insulator O.D.: 0.6 mm dia.

Construction: AWG #32 (7/0.075 mm)

7. ACCOMMODATED P.C.BOARD

0.8 mm (.031") ~ 1.6 mm (.063")



REVIEWED : Alex APPROVED : David VERIFIED : Rita .

ENGINEERING DEPT.	PRODUCT SPECIFICATION For 1.27 mm (.050") Center Spacing Flat Cable - IDC Dip Plug	SPEC.NO.: SPCA003B
		PAGE: 2/2

8. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	
8.1	Rated current and voltage		0.5 A 250V AC (r.m.s.)
8.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 30 mΩ
8.3	Dielectric strength	When applied AC 500 V 1 minute between adjacent terminal	No change
8.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Heat aging	105 ± 2°C , 96 hours	No damage
9.2	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 8-3
9.3	Temperature cycling	One cycle consists of : (1) -55 ⁺⁰ / ₋₃ °C , 30 min. (2) Room temp. 10-15 min. (3) 85 ⁺³ / ₋₀ °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial
9.4	Salt spray	Temperature: 35 ± 3°C Solution: 5 ± 1% Spray time: 48 ± 4 hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: Less than twice of initial

10. AMBIENT TEMPERATURE RANGE: -40 to + 105°C