



<b>ENGINEERING</b>	<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Center Spacing Flat Cable - IDC Shrouded and Box Header of system CA26</b>	<b>SPEC.NO.: SPCA008C</b>
<b>DEPT.</b>		<b>PAGE: 1/2</b>

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and below standards base on CviLux test procedure

2. APPLICABLE STANDARDS:

MIL - STD - 202                      Methods for test of connectors for electronic equipment  
MIL - STD - 1344                    Test methods for electrical connectors

3. APPLICABLE SERIES NO.: **CA26 Series**

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. APPLICABLE CABLES

1.27 mm (.050") center spacing Flat Cable

Insulator O.D.: 0.85 mm dia.

Construction: AWG #28 (7/0.127 mm)



REVIEWED : Alex    APPROVED : David    VERIFIED : Sun .

<b>ENGINEERING</b>  <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b> <b>For 2.54 mm (.100") Center Spacing Flat</b> <b>Cable - IDC Shrouded and Box Header</b> <b>of system CA26</b>	<b>SPEC.NO.: SPCA008C</b>
		<b>PAGE: 2/2</b>

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	
7.1	Rated current and voltage		1 A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max. , 100 mA max.	Less than 30 mΩ
7.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Pin retention force	Push pin from insulator base at speed 25± 3 mm per minute	More than 1.5 Kgf

**9. ENVIRONMENTAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Heat aging	105 ± 2°C , 96 hours	No damage
9.2	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3
9.3	Temperature cycling	One cycle consists of : (1) -55 <sup>+0</sup> / <sub>-3</sub> °C , 30 min. (2) Room temp. 10-15 min. (3) 85 <sup>+3</sup> / <sub>-0</sub> °C , 30 min. (4) Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial
9.4	Salt spray	Temperature: 35 ± 3°C Solution: 5 ± 1% Spray time: 48 ± 4 hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: Less than twice of initial

**10. AMBIENT TEMPERATURE RANGE: -40 to + 105°C**