

**ENGINEERING**  
**DEPT.**

**PRODUCT SPECIFICATION**  
**For 2.00mm Wire Holder Connector System**

**SPEC.NO.: SPCI023C**

**PAGE: 1 / 2**

**1. SCOPE:**

This specification contains the test requirement of subject wire holder connectors when tested under the condition and below standards base on CviLux test procedure

**2. APPLICABLE STANDARDS:**

MIL - STD - 202                      Methods for test of connectors for electronic equipment  
MIL - STD - 1344                    Test methods for electrical connectors

**3. APPLICABLE SERIES NO.: CI90 Series**

**4. SHAPE, CONSTRUCTION AND DIMENSIONS**

See attached drawings

**5. MATERIALS**

See attached drawings

**6. ACCOMMODATED P.C.BOARD**

6.1 Thickness: 1.6 mm (.063")

6.2 P.C. Board Layout: See attached drawings



REVIEWED : Alex APPROVED : David VERIFIED : Rita .

<b>ENGINEERING</b> <b>DEPT.</b>	<b>PRODUCT SPECIFICATION</b> <b>For 2.00mm Wire Holder Connector System</b>	<b>SPEC.NO.: SPCI023C</b>
		<b>PAGE: 2 / 2</b>

**7. ELECTRICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		1.5A 250V AC (r.m.s.)
7.2	Dielectric strength	When applied AC 1000V 1 minute between adjacent terminal	No change
7.3	Insulation resistance	When applied DC 500V between adjacent terminal or ground	More than 1000 MΩ

**8. MECHANICAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Wire retention force	Pull wire from insulator housing at speed 25±3mm per minute	More than 100 gram

**9. ENVIRONMENTAL PERFORMANCE:**

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Resistance to soldering heat	Soldering time: 5 ± 0.5 second Soldering pot: 260 ± 5°C	No damage
9.2	Heat resistance	85± 2°C, 96 hours	No damage
9.3	Humidity	40± 2°C, 90-95% RH, 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Dielectric strength: To pass para 7-2
9.4	Temperature cycling	One cycle consists of : (1) -55 <sup>+0</sup> <sub>-3</sub> °C , 30 min. (2) Room temp. 10-15 min. (3) 85 <sup>+3</sup> <sub>-0</sub> °C , 30 min. (4) Room temp. 10-15 min.	No damage

**10. AMBIENT TEMPERATURE RANGE : -55 to + 85°C**