

ENGINEERING DEPT.		PRODUCT SPECIFICATION For CI82 Series Friction Lock Breakaway Header System	SPEC.NO.: SPCI026E
REVISIONS	ECN10052		PAGE: 1/3

1. SCOPE:

This specification contains the test requirement of subject connectors when tested under the condition and procedure with terminals crimped on the specified maximum size wire

2. APPLICABLE STANDARDS:

MIL - STD - 202 Methods for test of connectors for electronic equipment
MIL - STD - 1344 Test methods for electrical connectors

3. APPLICABLE SERIES NO.: CI82 Series

4. SHAPE, CONSTRUCTION AND DIMENSIONS

See attached drawings

5. MATERIALS

See attached drawings

6. ACCOMMODATED P.C.BOARD

6.1 Thickness: 1.6 mm (.063")
6.2 P.C. Board Layout: See attached drawings



REVIEWED : David APPROVED : Eisley VERIFIED : Sandy .

ENGINEERING DEPT.		PRODUCT SPECIFICATION For CI82 Series Friction Lock Breakaway Header System	SPEC.NO.: SPCI026E
REVISIONS	ECN10052		PAGE: 2/3

7. ELECTRICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
7.1	Rated current and voltage		7A 250V AC (r.m.s.)
7.2	Contact resistance	Dry circuit of DC 20 mV max., 100 mA max.	Less than 20 mΩ
7.3	Dielectric strength	When applied AC 1000 V 1 minute between adjacent terminal	No change
7.4	Insulation resistance	When applied DC 500 V between adjacent terminal or ground	More than 1000 MΩ

8. MECHANICAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
8.1	Pin retention force	Push pin from insulator base at speed 25± 3 mm per minute	More than 3.0 Kgf

9. ENVIRONMENTAL PERFORMANCE:

	ITEM	TEST CONDITION	REQUIREMENT
9.1	Solder ability	Tin-Lead Process: Soldering time: 5 ± 0.5 second Soldering pot: 230 ± 5°C	Minimum: 90% of immersed area
9.2	Resistance to soldering heat	Tin-Lead Process: Soldering time: 5 ± 0.5 second Soldering pot: 240 ± 5°C	No damage
9.3	Heat aging	105 ± 2°C , 96 hours	No damage
9.4	Humidity	40 ± 2°C , 90-95% RH , 96 hours measurement must be taken within 30 min. after tested	Appearance: No damage Contact resistance: Less than twice of initial Dielectric strength: To pass para 7-3

ENGINEERING DEPT.		PRODUCT SPECIFICATION For CI82 Series Friction Lock Breakaway Header System	SPEC.NO.: SPCI026E
REVISIONS	ECN10052		PAGE: 3/3

	ITEM	TEST CONDITION	REQUIREMENT
9.5	Temperature cycling	One cycle consists of : (1)-55 ⁺⁰ / ₋₃ °C , 30 min. (2)Room temp. 10-15 min. (3) 85 ⁺³ / ₋₀ °C , 30 min. (4)Room temp. 10-15 min.	Appearance: No damage Contact resistance: Less than twice of initial
9.6	Salt spray	Temperature: 35 ± 3°C Solution: 5 ± 1% Spray time: 48 ± 4 hours Measurement must be taken after water rinse	Appearance: No damage Contact resistance: Less than twice of initial

10. AMBIENT TEMPERATURE RANGE: -40 to +105°C