

A = 2.00 * No. of Spaces
 B = A + 2.00
 * Available in 2 through 40 circuits

Recommended P.C. Board Layout

Notes:

- * Material:
Contact: Brass
- * Pin overall Length 30.0mm Max.
- * For Lead Free Wave Flow Process

Ordering Code


CH11 ** * V A ** -NH
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② No. of Circuits
- ③ Plating Code:
1 = 3.05 μm(120 μ") Min. Matte Tin
over 0.76 μm(30 μ") Nickel
2 = Gold flash plated
over 1.27 μm(50 μ") Nickel
- ④ V= Straight
- ⑤ Insulation: A= Nylon 6T UL 94V-0, Color Black
- ⑥ Pin Length Option code:
See Table PDF. File No. CH1101T
- ⑦ -NH= For Lead Free Wave Processes and
Halogen-Free

Halogen-Free

Lead Free Process

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: 2.00MM(.079") STRAIGHT	 瀚荃股份有限公司 CviLux Corporation
3					DRAWN BY: Aaron	TOLERANCE UNLESS OTHERWISE SPECIFIED	SINGLE ROW BORAD MOUNT PIN HEADER	
2					ENGINEER: Sun	.X ± 0.30 / .012 .X' ± 1'	MATERIAL:	DRAWING NO. CH1156SB PART NO. CH11***VA**-NH
1	Aaron	10/21-16'	ECNT116250/ECRB116072	CHECKED BY: Eisley	12/16-16'	.XX ± 0.20 / .008 .X' ±	FINISH:	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	12/16-16'	.XXX ± 0.10 / .004 .XX' ±	SCALE	4 / 1 SHEET 1 OF 1

CIVILUX CORP
 2016.12.22
 ISSUED