

A = 2.50 x No. of Spaces
 B = A + 5.0
 C = A + 3.5

* Available in 2 through 20 circuits

Note:

1. Material:
 ▲* Insulation: High Temperature Plastic
 UL 94V-0 Color Nature


* Contact: Brass

2. For Lead Free Wave flow Process
 ▲

Ordering Code:

CI22 ** P 1 H K0 - LF
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 1 = 3.05μm(120μ") Min. Matte Tin
 plated over 0.76μm(30μ") Nickel
- ⑤ Type: H= Right angle
- ⑥ Other Option: K0= With Pin Kinked
- ⑦ LF= For Lead Free Wave flow Process




Recommended P.C. Board Layout

Lead Free Process

RoHS Compliant

CVILUX CORP
 2013.04.24
 ISSUED

4					DATE	UNIT: mm / inch	TITLE: 2.50MM(.098") RIGHT ANGLE PIN HEADERS	 瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Enya	4/16-13'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2	Enya	4/16-13'	ECN13075-0/ECR13027-0	ENGINEER: Eisley	4/17-13'	.X ± 0.30/.012 X: ± r		
1	Enya	3/11-13'	ECN13056-0/ECR13007-1	CHECKED BY: Eisley	4/17-13'	.XX ± 0.20/.008 .X: ±	FINISH:	
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	4/17-13'	.XXX ± 0.10/.004 .XX: ±		DRAWING NO. CI2228SB
							SCALE 4 / 1	SHEET 1 OF 1