



Recommended P.C. Board Layout

Material:

- * Insulation: Nylon 6T
- * Contact: Brass
- * Circuit Pattern Schedule: See Drawing No: CP0110S*
- * For Lead Free wave flow process

Ordering Code:

CP-01 3 ** 1 * 0 -NH
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Type of Connector: 3= Straight PCB mount header
- ③ No. of Circuits: See below table
- ④ Plating Code:
 1= 2.54μm(100μ") Matte Tin over 0.76μm(30μ") Nickel
 2= Gold flash plated over 1.27μm(50μ") Nickel
- ⑤ Variation:
 3= Without mounting pegs
 5= With mounting pegs
- ⑥ Option:
 0= Standard
- ⑦ Other option:
 -NH= For Lead Free IR Processes and Halogen-Free

Halogen-Free
 Lead Free Process
 RoHS Compliant

④						DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER	瀚荃股份有限公司 CviLux Corporation	
③						10/28-16'	TOLERANCE UNLESS OTHERWISE SPECIFIED	CP-01 POWER CONNECTOR		
②						10/28-16'	.X ± 0.38/.015 X' ± r	MATERIAL:		
①	Hank	10/28-16	ECNT116260			10/28-16'	.XX ± 0.25/.010 X' ±	FINISH:		
SYM	NAME	DATE	REVISIONS			10/28-16'	.XXX ± 0.10/.004 XX' ±		DRAWING NO. CP01266SB	PART NO. CP-013****0-NH
									SCALE 2 / 1	SHEET 1 OF 1

