



Material:

Insulator: Glass filled Polyester UL 94V-0

Shell: Steel, Tin plated as standard

Ordering Code

C3W3 S0000 100 000
 ① ② ③ ④

- ① Series No.
- ② Connector Type:
S0000= Receptacle
- ③ Insulator Color:
100= Black
600= Green
- ④ Mounting Style:
000= With $\phi 3.05$ mm holes on shell
A00= Riveted #4-40 UNC close nuts on front shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style

RoHS Compliant

Code	000	Code	A00	Code	B00	Code	C00
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

4				DATE	UNIT: mm / inch	TITLE: C3W3 FEMALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	
2				ENGINEER: David	10/15-01'	.X ± 0.30/.012 X' ± 1"	DRAWING NO. C3W302SB PART NO. C3W3S0000*00*00 SCALE 2 / 1 SHEET 1 OF 1
1				CHECKED BY: David	10/15-01'	.XX ± 0.20/.008 .X' ±	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/15-01'	.XXX ± 0.10/.004 .XX' ±	

