



Material:

Insulator: Glass filled Polyester UL 94V-0

Shell: Steel, Tin plated as standard

Coaxial terminal

Insulator: Teflon UL 94V-0

Color white

Contact: Brass with Gold plated

Ordering Code

C3W3 S C V 3 0 1 75 D00
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: S= Receptacle
- ③ Contact type: C= Coaxial Contact
- ④ Contact tail style: V= Straight Dip type
- ⑤ Coaxial contact plating:
 2= Gold flash plated over Nickel
 3= 15μ" Gold plated over Nickel
 4= 30μ" Gold plated over Nickel
 5= 50μ" Gold plated over Nickel
- ⑥ Singal contact plating:
 0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 50= 50Ω, 75= 75Ω
- ⑨ Mounting Style:
 000= With ø3.05mm holes on shell
 B00= Riveted #4-40 UNC open nuts on front shell
 C00= Riveted #4-40 UNC open nuts on rear shell
 D00= Riveted #4-40 UNC ground stand-off on rear shell(standard)

Mounting Style

Code		000	Code		B00	Code		C00	Code		D00
		DIM. L= 4.0mm				DIM. L= 4.0mm				DIM. L= 7.0mm	

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: C3W3 COAXIAL FEMALE D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)	瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2				ENGINEER: David	10/15-01'	.X ± 0.30/.012 X' ± 1'	FINISH:	
1				CHECKED BY: David	10/15-01'	.XX ± 0.20/.008 .X' ±		
				APPROVED BY: Alex	10/15-01'	.XXX ± 0.10/.004 .XX' ±		
SYM	NAME	DATE	REVISIONS				DRAWING NO. C3W304SB	PART NO. C3W3SCV*0****00
							SCALE 2 / 1	SHEET 1 OF 1

CVILUX.CORP.
 2001.10.21
 ISSUED