



Material:  
 Insulator: Glass filled Polyester UL 94V-0  
 Shell: Steel, Tin plated as standard

Ordering Code

C5W5 P0000 100 000  
 ① ② ③ ④

- ① Series No.
- ② Connector Type:  
P0000= Plug
- ③ Insulator Color:  
100= Black  
600= Green
- ④ Mounting Style:  
000= With  $\phi 3.05$ mm holes on shell  
A00= Riveted #4-40 UNC close nuts on front shell  
B00= Riveted #4-40 UNC open nuts on front shell  
C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style				RoHS Compliant			
Code	000	Code	A00	Code	B00	Code	C00
		DIM. L= 5.8mm 		DIM. L= 4.0mm 		DIM. L= 4.0mm 	

4					DATE	UNIT: mm / inch	TITLE: C5W5 MALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	 瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2				ENGINEER: David	10/15-01'	.X ± 0.30/012 X: ± 1'		
1				CHECKED BY: David	10/15-01'	.XX ± 0.20/008 .X: ±	FINISH:	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/15-01'	.XXX ± 0.10/004 .XX: ±		



DRAWING NO.	C5W501SB	PART NO.	C5W5P0000*00***
SCALE	2 / 1	SHEET	1 OF 1