



Material:

Insulator: Glass filled Polyester UL 94V-0

Shell: Steel, Tin plated as standard

### Ordering Code

C5W5 S0000 100 000  
 ① ② ③ ④

- ① Series No.
- ② Connector Type:  
S0000= Receptacle
- ③ Insulator Color:  
100= Black  
600= Green
- ④ Mounting Style:  
000= With  $\phi 3.05$ mm holes on shell  
A00= Riveted #4-40 UNC close nuts on front shell  
B00= Riveted #4-40 UNC open nuts on front shell  
C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style				RoHS Compliant			
Code	000	Code	A00	Code	B00	Code	C00
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

4					DATE	UNIT: mm / inch	TITLE: C5W5 FEMALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2				ENGINEER: David	10/15-01'	.X ± 0.30/.012 X' ± 1'		
1				CHECKED BY: David	10/15-01'	.XX ± 0.20/.008 .X' ±	FINISH:	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/15-01'	.XXX ± 0.10/.004 .XX' ±		

CVILUX.CORP.  
 2001.10.22  
 ISSUED

DRAWING NO.	C5W502SB	PART NO.	C5W5S0000*00***
SCALE	2 / 1	SHEET	1 OF 1