



Material:

Insulator: Glass filled Polyester UL 94V-0
Shell: Steel, Tin plated as standard

Coaxial terminal

Insulator: Teflon UL 94V-0
Color white
Contact: Brass

Ordering Code

C5W5 P C V 3 0 1 75 D00
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: P= Plug
- ③ Contact type: C= Coaxial Contact
- ④ Contact tail style: V= Straight Dip type
- ⑤ Coaxial contact plating:
2= Gold flash plated over Nickel
3= 15 μ Gold plated over Nickel
4= 30 μ Gold plated over Nickel
5= 50 μ Gold plated over Nickel
- ⑥ Singal contact plating:
0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 50= 50 Ω , 75= 75 Ω
- ⑨ Mounting Style:
000= With ϕ 3.05mm holes on shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell
D00= Riveted #4-40 UNC ground stand-off on rear shell(standard)

Mounting Style

Code		Code		Code		Code	
000		B00		C00		D00	

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: C5W5 COAXIAL MALE D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)	 瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Eisley	10/09-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
2				ENGINEER: David	10/15-01'	.X \pm 0.30/012 X' \pm 1'	FINISH:	
1				CHECKED BY: David	10/15-01'	.XX \pm 0.20/008 .X' \pm		
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/15-01'	.XXX \pm 0.10/004 .XX' \pm		DRAWING NO. C5W503SB PART NO. C5W5PCV*0****00
								SCALE 2 / 1 SHEET 1 OF 1

CVILUX.CORP.
2001.10.22
ISSUED