



Material:  
Insulator: Glass filled Polyester UL 94V-0  
Shell: Steel, Tin plated as standard  
High power Contact : Brass with Gold plated

### Ordering Code

C5W5 P P V 3 0 1 40 D00  
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: P= Plug
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: V= Straight Dip type
- ⑤ High power contact plating:  
2= Gold flash plated over Nickel  
3= 15μ" Gold plated over Nickel  
4= 30μ" Gold plated over Nickel  
5= 50μ" Gold plated over Nickel
- ⑥ Singal contact plating:  
0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 40= 40A
- ⑨ Mounting Style:  
000= With Ø3.05mm holes on shell  
B00= Riveted #4-40 UNC open nuts on front shell  
C00= Riveted #4-40 UNC open nuts on rear shell  
D00= Riveted #4-40 UNC ground stand-off on rear shell(standard)

Mounting Style				RoHS Compliant			
Code	000	Code	B00	Code	C00	Code	D00
			DIM. L= 4.0mm		DIM. L= 4.0mm		DIM. L= 7.0mm

4																			
3																			
2																			
1																			
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Alex	10/19-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED	.X ± 0.30/012	.XX ± 0.20/008	.XXX ± 0.10/004	X' ± 1'	.X' ±	.XX' ±						
				DRAWN BY:	Rita	10/18-01'	UNIT: mm / inch				TITLE: C5W5 40A HIGH POWER MALE D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)				MATERIAL:				
				ENGINEER:	David	10/19-01'					FINISH:				DRAWING NO. C5W509SB PART NO. C5W5PPV*0*40***				
				CHECKED BY:	David	10/19-01'									SCALE 2 / 1 SHEET 1 OF 1				
				ISSUED											SHEET 1 OF 1				

CVILUX.CORP.  
2001.10.22  
ISSUED

瀚荃股份有限公司  
CviLux Corporation