



A = 2.54 * No. of Spaces
 B = A + 3.04
 * Available in 20, 32 circuits

Recommended P.C. Board Layout

Material:

- * Insulation: Glass filled polyester UL 94V-0
- * Contact: Phosphor Bronze

Ordering Code:

CB93 ** 2 V 1 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② NO. of Circuits:
- ③ Plating code:
 2= Gold flash plated over
 1.27μm(50μ") Nickel
- ④ Tail Style: V= Straight
- ⑤ Color: 1= Black
- ⑥ Other options: 00= Standard

Option Code	Dimension
	C
00	12.20(.480)
A0	2.30(.091)

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: 2.54MM(.100")	瀚荃股份有限公司 CviLux Corporation
3				DRAWN BY: Sandy	12/27-06'	TOLERANCE UNLESS OTHERWISE SPECIFIED	SINGLE ROW ELEVATED CONNECTOR	
2				ENGINEER: Eisley	12/29-06'	.X ± 0.30 / .012 X' ± 1"	MATERIAL:	DRAWING NO. CB9301SA PART NO. CB93**2V1**
1				CHECKED BY: David	12/29-06'	.XX ± 0.20 / .008 X' ±	FINISH:	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	12/29-06'	.XXX ± 0.10 / .004 XX' ±		SCALE 3 / 1 SHEET 1 OF 1

CVILUX CORP.
 2007.01.03
 ISSUED