

Material:

\* Insulation: Glass filled polyester UL 94V-0


\* Contact: Phosphor Bronze

Ordering Code:

CB96 \*\* 2 V 1 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② NO. of Circuits:
- ③ Plating code:  
 2= Gold flash plated over  
 1.27μm(50μ") Nickel
- ④ Tail Style: V= Straight
- ⑤ Color: 1= Black
- ⑥ Other options: 00= Standard

Option Code	Dimension	
	C	D
00	11.05(.435)	2.3(.091)
1Y	11.05(.435)	7.3(.287)
2Y	13.59(.535)	4.8(.189)
3Y	16.13(.635)	2.3(.091)
1Z	11.05(.435)	12.2(.480)
2Z	13.59(.535)	9.6(.378)
3Z	16.13(.635)	7.1(.280)
4Z	18.67(.735)	4.6(.181)
2W	13.59(.535)	3.4(.134)
2V	13.58(.535)	3.00(.118)



△	CIRCUITS	DIM.F
	6~40P	0.20 Max.
	42~80P	0.30 Max.



A = 2.54 \* No. of Spaces

B = A + 3.04

\* Available in 6 through 80 circuits

Recommended P.C. Board Layout

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: 2.54MM(.100") DUAL ROW ELEVATED CONNECTOR	 瀚荃股份有限公司 CviLux Corporation	
③					DRAWN BY: Karen	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:		
②	Karen	9/30-09'	ECN09203		ENGINEER: Easley	.X ± 0.30 / .012	X' ± 1"	DRAWING NO. CB9601SF	
①	Karen	6/27-08'	ECN08303		CHECKED BY: David	10/1-09'	.XX ± 0.20 / .008		.X' ±
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/1-09'	.XXX ± 0.10 / .004	.XX' ±	FINISH:	SCALE 3 / 1
								SHEET 1 OF 1	