



Materials:

- * Insulator: Glass filled polyester UL 94V-0
- * Contacts: Copper alloy
- * Shell: Steel, Tin plated as standard

Ordering Code :

$\frac{CD02}{①}$
 $\frac{26}{②}$
 $\frac{S}{③}$
 $\frac{0}{④}$
 $\frac{1}{⑤}$
 $\frac{00}{⑥}$

- ① Series No.
 - ② No. of Circuits
 - ③ Contact type: S= Receptacle(Female)
 - ④ Plating code:
 - ⑤ Color: 1= Black, 7= Blue, 0= White
 - ⑥ Mounting style:
- △ 00= With $\phi 3.00$ mm holes on shell(Standard)
 A0= Riveted #4-40 UNC close nuts on front shell
 B0= Riveted #4-40 UNC open nuts on front shell
 C0= Riveted #4-40 UNC open nuts on rear shell

Circuits	Dimension				
	A	B	C	D	E
15	25.00(.984)	30.8(1.213)	16.30(.642)	19.20(.756)	2.29(.090)
26	33.32(1.312)	39.2(1.543)	24.60(.969)	27.70(1.091)	2.29(.090)
44	47.04(1.852)	53.1(2.091)	38.30(1.508)	41.10(1.618)	2.29(.090)
62	63.50(2.500)	69.4(2.732)	54.80(2.157)	57.30(2.256)	2.41(.095)

Mounting Style				RoHS Compliant			
Code	00	Code	A0	Code	B0	Code	C0
		DIM. L= 5.8mm 		DIM. L= 4.0mm 		DIM. L= 4.0mm 	

④					DATE	UNIT: mm / inch	TITLE: HIGH-DENSITY D-SUB CRIMP TYPE FEMALE CONNECTOR	瀚荃股份有限公司 CviLux Corporation				
③					DRAWN BY: Sandy	3/26-10'	TOLERANCE UNLESS OTHERWISE SPECIFIED					
②					ENGINEER: Eisley	4/12-10'	.X ± 0.30/.012 X' ± 1'	MATERIAL:	DRAWING NO.	CD0201SD	PART NO.	CD02**S0***
①	Sandy	3/25-10'	ECN10079		CHECKED BY: David	4/12-10'	.XX ± 0.20/.010 .X' ±	FINISH:	SCALE	2 / 1	SHEET	1 OF 1
SYM	NAME	DATE	REVISIONS		APPROVED BY: David	4/12-10'	.XXX ± 0.10/.004 .XX' ±					

CVILUX CORP
 2010.04.27
 ISSUED