



Wire Range	Insulation Diameter	Reel Q'ty
AWG #26~#30	1.35 (.053) MAX.	15,000 PCS.

Ordering Code :

CD02 T01 A B P S  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Terminal version: T01= For AWG #26~#30
- ③ Plating code:  
 2= Gold flash plated over 1.27μm(50μ") Nickel  
 A= Selective Gold flash plated over 1.27μm(50μ") Nickel  
 B= Selective 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel  
 C= Selective 0.76um(30μ") Gold plated over 1.27μm(50μ") Nickel
- ④ Material: B= Brass
- ⑤ Plating method: P= Post plating
- ⑥ Type: S= Receptacle terminal

RoHS Compliant

SYM	NAME	DATE	REVISIONS	APPROVED BY:	DATE	UNIT: mm / inch	TITLE:	CviLux Corporation			
④	Sun	7/20-09'	ECR9077-1/ECN09354			UNIT: mm / inch	CRIMP TERMINAL	瀚荃股份有限公司 CviLux Corporation			
③	Karen	4/15-09'	ECR09041-1/ECN09194	DRAWN BY:	Karen	7/20-09'					
②	Sun	12/03-07'	ECR07151-3/ECN07466	ENGINEER:	Eisley	7/23-09'	MATERIAL:	DRAWING NO.	CD0205SH	PART NO.	CD02T01*BPS
①	Sandy	11/5/04'	ECN04435	CHECKED BY:	Eisley	7/23-09'	FINISH:	SCALE	5 / 1	SHEET	1 OF 1
				APPROVED BY:	Alex	7/23-09'					

CIVILUX CORP  
 2009.07.28  
 ISSUED