

Material:

- * Insulator: Glass filled polyester UL 94V-0
- * Contacts: Copper alloy
- * Shell: Steel, Tin plated as standard

Recommended P.C. Board Layout see drawing No. CD6113S*

Ordering Code:

CD62 25 S 2 1 F0
① ② ③ ④ ⑤ ⑥

① Series No.

② Contacts

③ Contact type: S= Receptacle(Female)

④ Plating option:

2= Gold flash plated over Nickel

A= Selective Gold flash plated over Nickel

B= Selective 0.38 μ m(15 μ "") Gold plated over
1.27 μ m(50 μ "") Nickel

C= Selective 0.76 μ m(30 μ "") Gold plated over
1.27 μ m(50 μ "") Nickel

⑤ Color: 1= Black


⑥ Other Option:

F0= Riveted ground hooks with #4-40 UNC open (Standard)

G0= Riveted ground hooks pre-loaded #4-40 UNC
Hex screws

I0= Riveted ground tabs thread #4-40 UNC open and
ground tabs with $\varnothing$ 3.2mm holes

J0= Assembly ground hooks by #4-40 UNC Hex screws



Circuits	Dimension		
	A	B	C
9	25.00(.984)	30.8(1.213)	16.30(.642)
15	33.32(1.312)	39.2(1.543)	24.60(.969)
25	47.04(1.852)	53.1(2.091)	38.30(1.508)
37	63.50(2.500)	69.4(2.732)	54.80(2.157)

Mounting Style

Code	F0	Code	G0	Code	I0	Code	J0
			DIM. L= 4.8mm		$\varnothing$ A= 3.2mm		DIM. L= 4.8mm

RoHS Compliant

4					DATE	UNIT: mm / inch	TITLE: D-SUB EITH FERRITE CORE PCB MOUNT (8.1mm) FEMALE CONNECTOR	 瀚菱股份有限公司 CviLux Corporation			
3					DRAWN BY: Eisley	10/24 01'	TOLERANCE UNLESS OTHERWISE SPECIFIED				
2					ENGINEER: David	10/29 01'	.X $\pm$ 0.30/.012 X' $\pm$ 1'	DRAWING NO. CD6201SD PART NO. CD62**S*1**			
1					CHECKED BY: David	10/29 01'	.XX $\pm$ 0.20/.010 .X' $\pm$				
SYM	NAME	DATE	REVISIONS	APPROVED BY: Alex	10/29 01'	.XXX $\pm$ 0.10/.004 .XX' $\pm$	FINISH:	SCALE	2 / 1	SHEET	1 OF 1

