

Materials:


- * Insulator: Glass filled polyester UL 94V-0
- * Contacts: Copper alloy
- * Shell: Steel, Tin plated as standard

Ordering Code:

CD67 09 P A 1 00
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Contacts:
- ③ Contact type: P= Plug(Male)
- ④ Plating option:
 2= Gold flash plated over 1.27μm(50μ) Nickel
 A= Selective Gold flash plated over 1.27μm(50μ) Nickel
 B= Selective 0.38μm(15μ) Gold plated over 1.27μm(50μ) Nickel
 C= Selective 0.76μm(30μ) Gold plated over 1.27μm(50μ) Nickel
- ⑤ Color: 1= Black
- ⑥ Other Option: 00= Standard

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: D-SUB TOP ENTRY BOARD MOUNT MALE CONNECTOR	 瀚荃股份有限公司 CviLux Corporation
③				DRAWN BY: Sun	12/1 03'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Eisley	12/2 03'	.X ± 0.30 / .012 X* ± 1"	FINISH:	DRAWING NO. CD6702SD
①	SUN	12/01/03'	ECN03434	CHECKED BY: David	12/2 03'	.XX ± 0.20 / .010 .X* ±		SCALE 2 / 1
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	12/3 03'	.XXX ± 0.10 / .004 .XX* ±		SHEET 1 OF 1


 CVILUX.CORP
 2003.12.03
 ISSUED