

Material:

Insulator: Glass filled Polyester UL 94V-0  
Color Black or White

Contact: Brass


Shell: Steel, Tin plated as standard

Ordering Code :

**CD72 50 P \* \* 00**  
① ② ③ ④ ⑤ ⑥

- Series No.
- Contacts: 50
- Contact type : P=plug , S=Receptacle
- Contact Plating :
  - 2 = Gold flash plated over 1.27 $\mu$ m(50 $\mu$ "") Nickel (Standard)
  - 3 = 0.38 $\mu$ m(15 $\mu$ "") Gold plated over 1.27 $\mu$ m(50 $\mu$ "") Nickel
  - 4 = 0.76 $\mu$ m(30 $\mu$ "") Gold plated over 1.27 $\mu$ m(50 $\mu$ "") Nickel
  - 5 = 1.27 $\mu$ m(50 $\mu$ "") Gold plated over 1.27 $\mu$ m(50 $\mu$ "") Nickel
- Insulator Color :
  - 1=Black , 0=White
- Other option :
  - 00 = With  $\phi 3.00$ mm holes on shell

RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: D-SUB TOP ENTRY MALE CONNECTOR (MACHINED CONTACTOR)	 瀚荃股份有限公司 CviLux Corporation
③				DRAWN BY: Sun	12/4 03'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Easley	12/4 03'	.X ±0.30/.012 X' ± 1'	FINISH:	DRAWING NO. CD7203SD PART NO. CD7250P**00
①	SUN	12/03/03'	ECN03437/ECR03056-0	CHECKED BY: David	12/4 03'	.XX ±0.20/.008 X' ±		SCALE 2 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS	APPROVED BY: David	12/4 03'	.XXX ±0.10/.004 X' ±		

CIVILUX.CORP  
2003.12.04  
ISSUED