



Notes:

Insulator: Glass filled Polyester UL 94V-0
 Shell: Steel, Tin plated as standard

Coaxial terminal

Insulator:Teflon UL 94V-0 Color white

Contact:Brass with Gold plated

*For Lead Free Wave Flow Process

Ordering Code

3W3C P C H 3 0 1 75 I10
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ① Series No.
- ② Connector Type: P= Plug (2 Male + 1 Female Contacts)
- ③ Contact type: C= Coaxial Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ Coaxial contact plating:
 2= Gold flash plated over Nickel
 3= 15μ" Gold plated over Nickel
 4= 30μ" Gold plated over Nickel
 5= 50μ" Gold plated over Nickel
- ⑥ Signal contact plating:
 0= Without signal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 50= 50Ω, 75= 75Ω
- ⑨ Mounting Style:
 000= With φ3.05mm holes on shell
 B00= Riveted #4-40 UNC open nuts on front shell
 C00= Riveted #4-40 UNC open nuts on rear shell
 I00= Riveted #4-40 UNC ground tabs with φ3.2mm holes
 I10= Riveted #4-40 UNC ground tabs with board locks(standard)

Mounting Style

Code	000	Code	B00	Code	C00	Code	I00	Code	I10
			DIM. L= 4.0mm		DIM. L= 4.0mm		φA=3.2mm		

Lead Free Process
 RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: 3W3C MALE COAXIAL D-SUB CONNECTOR (RIGHT ANGLE BOARD MOUNT TYPE)	瀚荃股份有限公司 CviLux Corporation
③					DRAWN BY: Karen 4/10-17'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②					ENGINEER: Sun 4/10-17'	.X ± 0.30/012 X: ± 1'	FINISH:	DRAWING NO. 3W3C14SB PART NO. 3W3CPCH*0*****0
①	Karen	4/07-17'	ECNT117049/ECRT117003		CHECKED BY: Eisley 4/14-17'	.XX ± 0.20/008 .X ±		SCALE 2 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS		APPROVED BY: Eisley 4/14-17'	.XXX ± 0.10/004 .XX ±		

CVILUX CORP
 2017.04.20
 ISSUED