


Notes:

Insulator: Glass filled Polyester UL 94V-0
 Shell: Steel, Tin plated as standard
 Coaxial terminal
 Insulator:Teflon UL 94V-0 Color white
 Contact:Brass with Gold plated
 *For Lead Free Wave Flow Process

Ordering Code



- ① Series No.
- ② Connector Type:
S= Receptacle (2 Female + 1 Male Contacts)
- ③ Contact type: C= Coaxial Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ Coaxial contact plating:
2= Gold flash plated over Nickel
3= 15μ" Gold plated over Nickel
4= 30μ" Gold plated over Nickel
5= 50μ" Gold plated over Nickel
- ⑥ Signal contact plating:
0= Without signal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 50= 50Ω, 75= 75Ω
- ⑨ Mounting Style:
000= With ø3.05mm holes on shell
B00= Riveted #4-40 UNC open nuts on front shell
C00= Riveted #4-40 UNC open nuts on rear shell
I00= Riveted #4-40 UNC ground tabs with ø3.2mm holes
I10= Riveted #4-40 UNC ground tabs with board locks(standard)

Mounting Style

Code	000	Code	B00	Code	C00	Code	I00	Code	I10
			DIM. L= 4.0mm		DIM. L= 4.0mm		øA=3.2mm		

Lead Free Process
 RoHS Compliant

SYM	NAME	DATE	REVISIONS
4			
3			
2			
1	Karen	4/07-17'	ECNT117049/ECRT117003

DRAWN BY:	ENGINEER:	CHECKED BY:	APPROVED BY:
Karen	Sun	Eisley	Eisley

DATE	UNIT:	TOLERANCE
4/10-17'	mm / inch	UNLESS OTHERWISE SPECIFIED
4/10-17'		.X ± 0.30/.012 X: ± 1'
4/14-17'		.XX ± 0.20/.008 .X: ±
4/14-17'		.XXX ± 0.10/.004 .XX ±

TITLE: 3W3C MALE COAXIAL D-SUB CONNECTOR (RHGHT ANGHT BOARD MOUNT TYPE)
 MATERIAL:
 FINISH:

瀚荃股份有限公司
 CviLux Corporation

DRAWING NO.	3W3C15SB	PART NO.	3W3CSCH*0*****0
SCALE	2 / 1	SHEET	1 OF 1

