

A = 2.50 x No. of Spaces  
 B = A + 5.0  
 C = A + 3.5


\* Available in 2 through 20 circuits

- Note: 1. Material:  
 \* Insulation: Nylon 66 UL 94V-0  
 Color Nature  
 \* Contact: Brass  
 2. For Tin-Lead Wave Flow Process

Ordering Code:

CI22 \*\* P 1 H K 0  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.  
 ② No. of Circuits  
 ③ Contact type: P= Pin header  
 ④ Plating option:  
 1= 3.05μm(120μ") Min. Tin  
 over 0.76μm(30μ") Nickel  
 ⑤ Type: H= Right angle  
 ⑥ Other Option: K= With Pin Kinked  
 ⑦ Process option:  
 For Tin-Lead Wave Flow Process



Recommended P.C. Board Layout

Tin-Lead Process

RoHS compliant

⑤	Enya	3/11-13'	ECN13056-0/ECR13007-1	 <b>2013.04.24</b> <b>ISSUED</b>		DATE	UNIT: mm / inch	TITLE: 2.50MM(.098")	 瀚荃股份有限公司 CviLux Corporation
④	Sandy	9/12/05'	ECN05297		DRAWN BY: Enya	3/11-13'	TOLERANCE UNLESS OTHERWISE SPECIFIED	RIGHT ANGLE PIN HEADERS	
③	SUN	03/05-04	ECN04093/ECR04007-1		ENGINEER: Eisley	3/12-13'	.X ± 0.30/.012 X' ± r	MATERIAL:	
②	SUN	11/20-03	ECN03408/ECR03021-1		CHECKED BY: Eisley	3/12-13'	.XX ± 0.20/.008 .X' ±	FINISH:	
SYM	NAME	DATE	REVISIONS		APPROVED BY: David	3/12-13'	.XXX ± 0.10/.004 .XX' ±		
DRAWING NO.		CI2203SN		PART NO.		CI22**P1HK0		SCALE	
SCALE		4 / 1		SHEET		1 OF 1			