



(2 through 5 circuits)

(6 through 20 circuits)

A = 2.54 x No. of Spaces

B = A + 2.54

\* Available in 2 through 20 circuits

Material:

\* Insulation: Nylon 66 UL 94V-2

Color Nature

\* Contact: Brass

Ordering Code:

CI31 \*\* P \* Y 00  
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:  
 1= 3.05μm(120μ") Min. Tin plated over 0.76μm(30μ") Nickel  
 2= Gold Flash plated over 1.27μm(50μ") Nickel  
 3= 0.38μm(15μ") Gold plated over 1.27μm(50μ") Nickel  
 4= 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ⑤ Tail Style: Y= Reverse Base
- ⑥ Option: 00= Standard

Recommended P.C. Board Layout

Tin-Lead Process

RoHS Compliant

④				CIVILUX CORP		DATE	UNIT: mm / inch	TITLE: 2.54MM(.100")	瀚荃股份有限公司 CviLux Corporation
③	Karen	8/05-08'	ECN08378	2008.08.06	DRAWN BY: Karen	8/05-08'	TOLERANCE UNLESS OTHERWISE SPECIFIED	REVERSE RIGHT ANGLE HEADERS	
②	Sandy	8/14/06"	ECN06275/ECR06020-2	ISSUED	ENGINEER: Eisley	8/05-08'	.X ± 0.30/.012 X: ± 1"	MATERIAL:	DRAWING NO. CI3104SH PART NO. CI31**P*Y00
①	SUN	2/11/04'	ECN04063		CHECKED BY: David	8/05-08'	.XX ± 0.20/.008 X: ±	FINISH:	SCALE 2 / 1 SHEET 1 OF 1
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	8/05-08'	.XXX ± 0.10/.004 X: ±		