



Recommended P.C. Board Layout

Material:

* Insulation: Nylon 66 UL 94V-2
 Color Nature

* Contact: Brass

Ordering Code:

CI54 ** P 1 V OM
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits: 02 to 10
- ③ Contact type: P= Pin header
- ④ Plating option:
 1= Tin Plated over Nickel
- ⑤ Tail Style: V= Straight
- ⑥ Other Option: OM= Standard
 (Glow wire available)

Circuits	Dimension	
	A	B
2	5.00(.197)	10.0(.394)
3	10.00(.394)	15.0(.591)
4	15.00(.591)	20.0(.787)
5	20.00(.787)	25.0(.984)
6	25.00(.984)	30.0(1.181)
7	30.00(1.181)	35.0(1.378)
8	35.00(1.378)	40.0(1.574)
9	40.00(1.574)	45.0(1.771)
10	45.00(1.771)	50.0(1.969)

Tin-Lead Process

RoHS Compliant

					DATE	UNIT: mm / inch	TITLE: 5.00mm (.197") STRAIGHT HEADER		瀚荃股份有限公司 CviLux Corporation			
					DRAWN BY: Sun	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:					DRAWING NO. CI5407SB
					ENGINEER: Sun	.X ± 0.38 / .015	X: ± 1"	FINISH:	SCALE	2 / 1	SHEET	1 OF 1
	Sun	4/21-16'	ECRH116017/ECNT116083		CHECKED BY: Eisley	.XX ± 0.25 / .010	.X: ±					
SYM	NAME	DATE	REVISIONS		APPROVED BY: Eisley	.XXX ± 0.15 / .006	.XX: ±					

CIVILUX CORP
2016.04.28
ISSUED