



Recommended P.C. Board Layout

Material:
 * Insulation: Nylon 66 UL 94V-2
 Color Nature
 * Contact: Brass

Ordering Code:

CI55 ** P 1 H OM
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② No. of Circuits
- ③ Contact type: P= Pin header
- ④ Plating option:
 1= 3.05µm(120µ") Min. Tin
 over 0.76µm(30µ") Nickel
- ⑤ Tail Style: H= Right angle
- ⑥ Other option: OM= Standard
 (Glow wire available)

Circuits	Dimension		
	A	B	△
2	5.08(.200)	10.08(.397)	
3	10.16(.400)	15.16(.597)	
4	15.24(.600)	20.24(.797)	
5	20.32(.800)	25.32(.997)	
6	25.40(1.00)	30.40(1.197)	
7	30.48(1.20)	35.48(1.397)	
8	35.56(1.40)	40.56(1.597)	
9	40.64(1.60)	45.64(1.797)	
10	45.72(1.80)	50.72(1.997)	

CVILUX CORP
 2016.04.29
 ISSUED

Tin-Lead Process RoHS Compliant

△4					DATE	UNIT: mm / inch	TITLE: 5.08mm (.200") RIGHT ANGLE HEADER
△3				DRAWN BY: Sun	4/21-16'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:
△2				ENGINEER: Sun	4/21-16'		
△1	Sun	4/21-16'	ECRH116017/ECNT116083	CHECKED BY: Eisley	4/22-16'	.X ± 0.38 / .015	.X' ± 1"
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	4/22-16'	.XX ± 0.25 / .010	.X' ±
						.XXX ± 0.15 / .006	.XX' ±



瀚荃股份有限公司
 CviLux Corporation

DRAWING NO.	CI5516SB	PART NO.	CI55**P1HOM
SCALE	2 / 1	SHEET	1 OF 1