


7. MATERIAL: COPPER ALLOY.
6. WHEN \*\* = 22 PLATING IS NICKEL.  
\*\* = 44 PLATING IS GOLD.  
\*\* = 77 PLATING IS TIN.
5. SEE 0425-015-0000 FOR CONTACT PERFORMANCE AND WIRE APPLICATION CHARACTERISTICS.
4. THIS CONTACT MAY BE CRIMPED WITH DCT20-02-00, DCT1620-02-00 AUTOMATIC DIE OR DTT-20-00 HAND TOOL. SEE DRAWING 0425-207-0000 FOR APPLICABLE WIRE SIZE, INSULATION DIAMETER RANGE, AND CRIMPING INFORMATION.
3. ONE REEL CONTAINS APPROXIMATELY 4000 CONTACTS.
2. DIMENSIONAL TOLERANCE:  $\pm .025$  [0.64].
1. DIMENSIONS ARE IN INCHES [mm].  
NOTES: UNLESS OTHERWISE SPECIFIED

REV		REVISIONS			
E		1062-20-03**	SYM	DESCRIPTION	DATE APPROVED
			B	REVISED PER E.O. P17023	12-8-00 R.D.R.
			C	REVISED PER E.O. P17843	3-8-04 R.D.R.
			D	REVISED PER E.O. P19555	7-11-07 R.D.R.
			E	REVISED PER E.O. P20392	12-3-09 RDR

SIGNATURE & DATE		STAMPED CONTACT SIZE 20 SLEEVELESS	EP		MATL. CODE			
DR	J. APOSTOL 02DEC2009		 3850 INDUSTRIAL AVE. HEMET, CA 92545	<b>DEUTSCH</b> INDUSTRIAL				
CHK	D. May 12/05							
PE	D. May 12/05							
APPD	R. Red 12-3-09							
SCALE NONE		WT		ENVELOPE		DWG SIZE	CODE 11139	SHEET 1 OF 1