REV	
E	DRC16-70SD *

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
B	REVISED PER E.O. P15967	03/23/99	RDR
C	REVISED PER E.O. P16064	04/20/99	RDR
D	REVISED PER E.O. P16775	7-27-00	RDR
E	REVISED PER E.O. P17732	4-15-02	RDR







8. MATERIAL- PLUG: PLASTIC (BLACK); SEAL/GROMMET: RUBBER; BOLT/CLIP: STEEL
7. MATING TORQUE REQUIREMENT: 25-28 IN-LB [2.82-3.16 Nm].
6. WHEN *=E: BLUE STRIP IDENTIFIES "E" SEAL.
5. THIS PLUG MATES WITH DRC12-70PD*-****; DRC13-70PD-****; DRC14-70PD*-****. (****= ALL MODIFICATIONS) CONSULT FACTORY FOR MODS.
4. FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS, SEE ENVELOPE DRAWING 0425-015-0000.
3. PLUG IS SUPPLIED WITH DUST CAP (NOT SHOWN).
2. DIMENSION TOLERANCE: ±.025 [.635].
1. DIMENSIONS ARE IN INCHES [mm].

NOTES:

6 SEAL TYPE	CONTACT SIZE	MIN. INSUL. OD [mm]	MAX. INSUL. OD [mm]	WIRE RANGE [mm^2] REF ONLY 4
NORMAL	16	.100 [2.540]	.134 [3.404]	14-18 AWG [2.0-.75]
E	16	.053 [1.346]	.120 [3.048]	14-20 AWG [2.0-.50]

	SIGNATURE & DATE
DR	D. MEYER 03/15/99
CHK	B. Byrd 4/15/02
PE	D Meyer 4/15/02
APPD	R. Rod 4-15-02
SCALE 1:1	WT

PLUG CONNECTOR
DRC 70 SERIES
KEY ARRANGEMENT -D-

ENVELOPE

CP | MATL. CODE

The Deutsch Company
DEUTSCH I.P.D.
3850 INDUSTRIAL AVE.
HEMET, CALIF. 92545

B DWG SIZE | DRC16-70SD * | CODE 11139 | SHEET 1 OF 1