


REV
B DRC18-40SC *

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
NC	NEW RELEASE PER E.O. A09233	10-16-90	J.A.
A	REVISED PER E.O. P15940	3-31-99	RDR
B	REVISED PER E.O. P16762	7-21-00	RDR



TOP VIEW

8. MATERIAL- PLUG: PLASTIC (BLACK); SEAL/GROMMET: RUBBER; BOLT/CLIP: STEEL.

7. MATING TORQUE REQUIREMENT: 25-28 IN-LB [2.82-3.16Nm].

△ WHEN *=E: BLUE STRIP IDENTIFIES "E" SEAL.

5. THIS PLUG MATES WITH DRC12-40PC*-****; DRC13-40PC-****; DRC14-40PC*-**** (****=ALL MODIFICATIONS). CONSULT FACTORY FOR MODS.

△ FOR CONTACTS AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS, SEE ENVELOPE DRAWING 0425-015-0000.

3. PLUG SUPPLIED WITH DUST CAP. (NOT SHOWN).

2. DIMENSION TOLERANCE: ±.025 [.635].

NOTES: 1. DIMENSIONS ARE IN INCHES [mm].

△ SEAL TYPE	CONTACT SIZE	MIN. INSUL. OD [mm]	MAX. INSUL. OD [mm]	WIRE RANGE [mm ²] REF ONLY △
NORMAL	16	.100 [2.540]	.134 [3.404]	14-18 AWG [2.0-.75]
E	16	.053 [1.346]	.120 [3.048]	14-20 AWG [2.0-0.50]

SIGNATURE & DATE	
DR	J. APOSTOL 13 JUL 2000
CHK	D. Meyer 7/21/00
PE	D. Meyer 7/21/00
APPD	R. Reed 7-21-00
SCALE	NONE WT

PLUG
KEY ARRANGEMENT -C-
SERVICEABLE CONTACTS
DRC 40 SERIES

ENVELOPE

CP	MATL. CODE
The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545	
B	DRC18-40SC *
DWG SIZE	CODE 11139 SHEET 1 OF 1