


SEE KEY ORIENTATION

4. THIS CONNECTOR WILL ACCOMMODATE THE FOLLOWING:

CONTACT SIZE	MIN. INSUL. O.D.	MAX. INSUL. O.D.	WIRE GAUGE RANGE REF ONLY 
20	.040 [1.016]	.095 [2.413]	16 THRU 20 [1.00-.50mm <sup>2</sup> ]

3. PLUG IS SUPPLIED WITH DUST CAP (NOT SHOWN).

2. DIMENSION TOLERANCE:  $\pm .025$  [.64].

1. DIMENSIONS ARE IN INCHES [mm].

NOTES: UNLESS OTHERWISE SPECIFIED

REV  
C

DRC26-24S\*-P019

# REVISIONS

SYM	DESCRIPTION	DATE	APPROVED
NC	NEW RELEASE PER E.O. P15540	2-24-98	R.D.R.
A	REVISED & REDRAWN PER E.O. P18099	4-7-03	R.D.R.
B	REVISED PER E.O. P18686	9-20-04	D.M.
C	REVISED PER E.O. P20729	12-6-10	RDR

DRC26-24SA-P019



DRC26-24SB-P019



DRC26-24SC-P019



DRC26-24SD-P019




8. MATERIAL: HOUSING: PLASTIC (BLACK); BOLT: STAINLESS STEEL; CLIP: STEEL WITH TRIVALENT CHROMATE OVER ZINC FINISH (-P019); GROMMET: RUBBER.

7. THIS PLUG MATES WITH DRC23-24P\*-\*\*\*\* RECEPTACLE. (\* = A,B,C,D KEYS; \*\*\*\* = ALL MODIFICATIONS)

 6 FOR CONTACT AND WIRE PERFORMANCE AND APPLICATION CHARACTERISTICS SEE ENVELOPE DRAWING 0425-015-0000.

5. RECOMMENDED RETAINING BOLT TORQUE: 25-28 IN-LB [2.82-3.16 NM].

SIGNATURE & DATE		PLUG 24 CONTACTS, SIZE 20 -P019 MOD DRC SERIES	EP	MATL. CODE		
DR	J. APOSTOL 31MAR2003		 3850 INDUSTRIAL AVE. HEMET, CA 92545 <b>DEUTSCH</b> INDUSTRIAL			
CHK	<i>Paula Carval</i> 12/6/10					
PE	<i>Paula Carval</i> 12/6/10					
APPD	<i>DM</i> 12/6/10		<b>B</b>	<b>DRC26-24S*-P019</b>		
SCALE	NONE (WT)	DWG SIZE 11139				

ENVELOPE	
----------	--