



REV	C	REVISIONS			
		SYM	DESCRIPTION	DATE	APPROVED
		NC	NEW RELEASE PER E.O. A11152	08/27/91	J.R.A.
		A	REVISED & REDRAWN PER E.O. P16453	12/17/99	R.D.R.
		B	REVISED PER E.O. P17741	12/27/02	R.D.R.
		C	REVISED PER E.O. P18557	5-3-04	RDR

4. FOR "PERFORMANCE AND APPLICATION CHARACTERISTICS OF SOLID/STAMPED AND FORMED CONTACTS AND WIRES," SEE ENVELOPE DRAWING 0425-015-0000. THIS PLUG USES SOCKET CONTACTS ONLY.

3. ALL DIMENSIONS ARE IN INCHES [MILLIMETERS].

2. THIS CONNECTOR SERIES WILL ACCOMMODATE THE FOLLOWING WIRE INSULATION DIAMETERS:

CONTACT SIZE	MINIMUM O.D.	MAXIMUM O.D.
16	.100 [2.54]	.150 [3.81]

1. CONSULT FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATIONS.
NOTES:

7. MATERIAL: SHELL: PLASTIC; SEAL: RUBBER.

6. OVERALL DIMENSIONS DOES NOT INCLUDE RUBBER GROMMET.

5. THIS PLUG MATES WITH HD10-9-96P*-**** AND HD14-9-96P*-**** RECEPTACLES (* = SEAL TYPE, **** = ALL MODIFICATIONS).

SIGNATURE & DATE		PLUG CONNECTOR HD10 SERIES ARR. 9-96 -C016 MOD. COLOR: GREY ENVELOPE	CP	MATL. CODE
DR	J. HAYNES 12/08/99		The Deutsch Company DEUTSCH I.P.D. 3850 INDUSTRIAL AVE. HEMET, CALIF. 92545	
CHK	James C. Gant 1/24/00			
PE	SBand 9-16-04		B HD16-9-96S-C016	
APPD	SBand 9-16-04			
SCALE	NONE	WT	DWG SIZE	CODE 11139 SHEET 1 OF 1