



6. PART MODIFICATION:
3 SIZE 4: 4 AWG [21.0-25.0 mm²] AND 4 SIZE 16.
5. RECEPTACLE IS SUPPLIED WITH DUST CAP (2415-001-2405).
- 4 NOTED DIMENSION DOES NOT INCLUDE GROMMET PROTRUSION.
- 3 MATERIAL: RECEPTACLE HOUSING: PA66 GF10 (BLACK)
RETAINER RING: PA66 GF10 (GREEN, GRAY, BLUE)
GROMMET: SILICONE (ORANGE-RED)
- 2 SEE 0425-021-0000 APPLICATION SPECIFICATION
A. RECOMMENDED WIRE INSULATION RANGE
B. CONTACT REMOVAL TOOLS
C. RECOMMENDED MOUNTING HOLE & PANEL THICKNESS
D. MOUNTING HARDWARE & MOUNTING TORQUE.

1. THIS RECEPTACLE MATES WITH HDP26-24-7SX-XXXX PLUG
X = SEAL TYPE (N,T,E)
XXXX = MODIFICATION

NOTES:

TE INTERNAL PN	DEUTSCH PN
HDP24-24-7PN-C038	HDP24-24-7PN-C038

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 01APR2010 ILINA GRANICHAROVA	TE Connectivity		
DIMENSIONS: INCHES[mm]		CHK 21JUL2010 JAIME C. APOSTOL			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 12JUL2010 STEVE BEARD	NAME RECEPTACLE, THREADED SIZE 24, -C038 MOD HDP SERIES		
0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ±.015 [0.38] 4 PLC ± ANGLES ±0°30'0"		PRODUCT SPEC 0425-021-0000	SIZE A3		
MATERIAL 3		APPLICATION SPEC 2	CAGE CODE 4AFU8		
FINISH N/A		WEIGHT 48.28g	DRAWING NO G-HDP24-24-7PN-C038		
		Customer Drawing	RESTRICTED TO -		
			SCALE 2:1 SHEET 1 OF 1 REV B		